

# OD3-600/6000

#### **PRODUCT OVERVIEW**

The OD3-600/6000 covers all Global Cellular & LTE frequencies and is also Private LTE and 5-G ready. Specifically, the Sub-6 Cellular/LTE element covers: 617-960 & 1710-6000 MHz. In addition, this antenna offers superior omni-directional coverage for 4G LTE.

Using the latest PCB technology, these antennas improve high-speed broadband system performance. This design maintains an omni pattern in the horizontal plane.

The OD Series are free space antennas; no groundplane is required. The antennas can be directly outfitted with coax cable so no additional jumpers are required. A variety of connectors can be used for the final termination.

The fiberglass radome (1" diameter/2.5 cm) makes the antennas durable and rugged. They can withstand the harshest environments of snow, wind, rain and ice.

The OD Series Antennas are supplied with all the hardware needed to install them to a mast. The OD antennas normally terminate with a female N connector.

Visit our eStore to customize an Antenna Online.

| Specifications              |                                    |
|-----------------------------|------------------------------------|
| Frequency & Gain            | 617-960 MHz, 2 dBi                 |
|                             | 1700-6000 MHz, 4 dBi               |
| Vertical Bemwidth<br>(-3dB) | (                                  |
| VSWR                        | <2:1                               |
| Radome Material             | Black Fiberglass                   |
| Nominal Impedance           | 50 ohms                            |
| Maximum Power               | 10 Watts                           |
| Connector                   | N Jack Female                      |
| Lightening Protection       | External Recommended               |
| Mounting (Kit Included)     | Mounts up to 2 1/2" OD Pipe        |
| Dimensions                  | 17.5" (444.5mm H x 1" (25.4mm) Dia |
| Wind Rating                 | 100 mph                            |
| Temperature                 | -40° C to +85° C                   |
| IP Rating                   | IPx5                               |



Sub-6, 5G Ready, Heavy Duty Omni-Direcitonal

### **HIGHLIGHTS:**

- Sub-6, 5G Ready OD
- 617-960 MHz & 1700-6000 MHz
- 2-4 dBi Gain
- Made-in-the-USA & UK

## **RELATED MODELS:**

- OD3-700/2700 ( Same Radome, Smaller Freq.)
- OD3-700/2700DN (Direct 'N' option, Smaller Freq.)
- OD3-600/6000MOD2 (Foam Filled Version)

#### **COMMON MARKETS:**

- · Rugged Mobile Wireless Networking
- Fixed Site Installation or Mobile
- Sub-6, 5G mm626 Solution



US Headquarters +1.847.671.6690 US/CA Toll Free +1.800.648.2800 European Facility +44.1543.459555

www.MobileMark.com